



Boss Flooring - BossLOC LVT Woodland Plank TECHNICAL DATA

SPECIFICATION	PLANK
Size	6" x 48"
Overall Thickness	6.5mm
Wear layer Thickness	20 mil (0.5 mm)
Wear layer Material	Vinyl / ArmourBead
Construction Material	Class III High Performance EVP
Pieces Per Carton	10/carton
Square Feet Per Carton	19.44
Carton Weight	30 lbs

COMMERCIAL TEST INFORMATION	
Slip Resistance - ASTM D2047	>0.6
Dimensional Stability - ASTM F2199	Less than 0.020"/ft at 140°F (60°C)
Risidual Indentation - ASTM F1914	Passes
Static Load - ASTM F970	Passes
Resistance to Heat - ASTM F1514	Passes
Resistance to Light - ASTM F1515	Passes
Resistance to Chemicals - ASTM F925	5 min = No Change 24 Hours = No Change
Castor Chair Resistance - NALFA 3.9	Passes 25,000 cycles
Radiant Flux ASTM 648	>0.45 watts/cm 2 NFPA Class 1
Smoke Density - ASTM E662	Passes <450
TESTING WITH UNDERLAYMENT	
Impact Insulation Class - IIC Rating	69 db
Sound Transmission Class - STC Rating	69 db

Warranty	10 Year Commercial, Lifetime Residential
Environmental - Indoor Air Quality	FloorScore® certified