



Boss Flooring - Command Series Vinyl Plank

TECHNICAL DATA

| SPECIFICATION | PLANK |
|------------------------|-----------------------------------|
| Size | 4" x 36" and 6" x 36" |
| Overall Thickness | 2.0mm |
| Wear layer Thickness | 20 mil |
| Wear layer Material | Vinyl / bossGUARD |
| Construction Material | Laminated Vinyl |
| Pieces Per Carton | 4" - 36/carton and 6" - 24/carton |
| Square Feet Per Carton | 36 |
| Carton Weight | 27 lbs. |

| COMMERCIAL TEST INFORMATION | |
|--|---|
| Slip Resistance | ADA Approved |
| ASTMD-2047-93 | ADA Approved |
| Static Load | 2000 psi |
| ASTM F970 | Passes |
| Resistance to Taber Abrasion | 3000cy. |
| ASTMD-1044-94 | 19.8 milligram weight loss |
| Resistance to Impact | Passed |
| FED.STD.501 Method 3311 | 4 of 4 Impacts |
| Critical Radiant Flux ASTME 648-94A, NEPA 253, FTM No.372, NBSIR 75-950 | Class I |
| Smoke Density Test | 450 |
| ASTME 662 | |
| Surface Burning Characteristics of Burning Material ASTME-84-94 | Class A |
| Maintenance | Normal Commercial Maintenance Required. See Instructions For Details. |
| Warranty | 15 Year Commercial, Lifetime Residential |
| Vinyl | Asbestos Free |
| Adhesive | Use Taylor 2091 or Mapei Eco 350 |
| Chemical Testing | Call Boss Flooring For Complete Testing Information |
| | Acoustical Tests Available |
| | *Call Boss Flooring for test results |