



## Boss Flooring - Hutton Porcelain Tiles

### TECHNICAL DATA

Size	12" x 24"
Thickness	3/8"
Construction Material	Glazed Porcelain
Coefficient of Friction (ASTM C1028)	>=.70 Dry >/.60 Wet

FEATURES	STANDARD	VALUE REQUIRED BY EN 14411 STANDARD	AVERAGE VALUE
Dimensional features	ISO 10545-2		Conforms to standard
Water Absorption	ISO 10545-3	<.5%	0.1%
Modulus of Rupture	ISO 10545-4	>35 N/mm <sup>2</sup>	45–60 N/mm <sup>2</sup>
Breaking Strength		>1300 N	1800–2500 N
Resistance to Surface Abrasion	ISO 10545-7	Indicated by manufacturer	According to models
Linear Thermal Expansion	ISO 10545-8	Test method available	<7,0 x 10 <sup>-6</sup> °C <sup>-1</sup>
Thermal Shock Resistance	ISO 10545-9	Test method available	Resists
Crazing Resistance	ISO 10545-11	Required	Resists
Frost Resistance	ISO 10545-12	Test method available	Resists
Chemical Resistance – Acids and bases	ISO 10545-13	Test method available	Conforms to standard
Chemical Resistance – Cleaning products and pool reactive agents		Minimum GB	Class GA
Stain Resistance	ISO 10545-14	Minimum class 3	Conforms to standard

